

Billi Spring 500+ Bottling System Specification Sheet



Instant chilled & sparkling filtered water.

Practical, reliable and visually striking, this innovative tap brings a high capacity refreshment solution to any commercial space.

Adjustable sparkling water

Adjust the level of sparkling to suit your taste with adjustable controls up to 5 bar of CO₂ pressure.

Adjustable chilled temperature

Fixed electronic controlled to optimum temperature.

Higher dispense height

Will fill even narrow neck bottles up to 310mm high. Fast and efficient.

Higher volume

Up to 80 litres of chilled or sparkling water dispensed per hour. Ideal for board rooms, meeting rooms, receptions and other areas of high volume chilled and sparkling requirement. The system is adjustable for taste which gives the equivalent of 250-350 glasses of water per 1.1kg cylinder. Packaging to include CO₂ canister.

POWER: 1 x single 13amp power socket

WATER: potable main water supply terminated with valve

DRAINAGE: drainage connection for drainage front drip tray connection

VENTILATION: Unit requires ventilation. For more information please download the Billi Spring 500+ Bottling System Install Guide.



Specifications and guide to standard model selection

Product Number	Description	Suggested no. of persons	Chilled & sparkling litres/ hour	Boiling cups / hour	Power required (amps)	Unit Height (mm)	Unit Width (mm)	Unit Depth (mm)
829100UK	Billi Spring 500+ Bottling System	500+	80	n/a	1 x13	600	455 incl handles	360 incl spacer & overflow

Shaw House,
Shaw Park,
Shaw Rd,
Wolverhampton,
WV10 9LE

020 7456 6789
marketing@billi-uk.com
www.billi-uk.com

London Showroom:
56-58 Clerkenwell Road,
Clerkenwell,
London,
EC1M 5PX

As Billi (UK) LLP has a policy of continual improvement, all details are subject to change without notice. All goods are sold subject to our published terms and conditions.

Billi is a registered trademark.
© 2018

BS500+BSDS062018